



# Battery Cables

For use in starter or battery ground circuits in accordance with SAE J-1127

Recommended Temperature Range: -40°C to +80°C

Standard Battery Circuit Colors: Black and Red

Full Gauge Copper Conductor

Spool Size: 100 feet

	Part No	# of Strands	Insulation Thickness	Diameter (in) Nominal	Approximate Net Weight
<b>6 GAUGE</b>	WSGT6RD	37	.060	.315	105
	WSGT6BK	37	.060	.315	105
<b>4 GAUGE</b>	WSGT4RD	61	.065	.360	160
	WSGT4BK	61	.065	.360	160
<b>2 GAUGE</b>	WSGT2RD	133	.065	.440	243
	WSGT2BK	133	.065	.440	243
<b>1 GAUGE</b>	WSGT1RD	133	.065	.480	303
	WSGT1BK	133	.065	.480	303
<b>1/0 GAUGE</b>	WSGT1/ORD	133	.065	.520	374
	WSGT1/OBK	133	.065	.520	374
<b>2/0 GAUGE</b>	WSGT2/ORD	133	.065	.570	463
	WSGT2/OBK	133	.065	.570	463
<b>3/0 GAUGE</b>	WSGT3/ORD	266	.078	.676	603
	WSGT3/OBK	266	.078	.676	603
<b>4/0 GAUGE</b>	WSGT4/ORD	418	.078	.740	749
	WSGT4/OBK	418	.078	.740	749