



SPIRALITE SPRAY HOSE



SPIRALITE 310

- » Yellow PVC ribbed cover and smooth tube with woven fabric reinforcement
- » Best combination of flexibility, durability, and value
- » General applications include agricultural spraying, pest control, and transferring compressed water and air
- » -10°F to +130°F temperature range
- » 570 PSI maximum working pressure; 1710 PSI design burst pressure
- » 300ft standard length

PART NO.	HOSE ID	IN DIA	OUT DIA	APPROX WEIGHT (LBS/300')
SPH310-1/4	1/4	19/64	17/32	24
SPH310-3/8	3/8	25/64	43/64	35
SPH310-1/2	1/2	33/64	13/16	47
SPH310-5/8	5/8	40/64	31/32	64
SPH310-3/4	3/4	3/4	1-5/64	80



SPIRALITE 320

- » Orange PVC ribbed cover, smooth tube with spiral yarn reinforcement construction
- » Durable and flexible
- » General applications include agricultural spraying, pest control, and transferring compressed water and air
- » -10°F to +130°F temperature range
- » 560 PSI maximum working pressure; 1710 PSI design burst pressure
- » 300ft standard length

PART NO.	HOSE ID	IN DIA	OUT DIA	APPROX WEIGHT (LBS/300')
SPH320-3/8	3/8	25/64	43/64	36
SPH320-1/2	1/2	33/64	13/16	48
SPH320-3/4	3/4	3/4	1-5/64	80



SPIRALITE 340

- » Green PVC ribbed cover, smooth tube with woven fabric reinforcement
- » High working pressure in a light weight, flexible package
- » General applications include agricultural spraying, pest control, and transferring compressed water and air
- » -10°F to +130°F temperature range
- » 560 PSI maximum working pressure
- » 300ft standard length

PART NO.	HOSE ID	IN DIA	OUT DIA	DESIGN BURST PRESSURE	APPROX WEIGHT (LBS/300')
SPH340-3/8	3/8	25/64	43/64	3700	41
SPH340-1/2	1/2	33/64	13/16	3500	54
SPH340-3/4	3/4	3/4	1-5/64	2700	91
SPH340-1	1	1	1-15/32	2460	135



IF-168 Spiralite Spray Hoses | \$40 minimum purchase on all sales orders
 211 Carter Drive, Suite B, West Chester, PA 19382 | 610-429-8266
www.kellyindustrial.com | www.kellyindustrialcatalog.com