

BLACK RUBBER PUSH-ON HOSE



- » Low pressure transmissions of oil, gas, air, water, coolants, and more applications
- » Black oil and weather-resistant synthetic rubber cover
- » Nitrile inner tube
- » Reinforcement: One textile braid
- » Temperature Range: -40°F to +212°F
- » Minimum Burst Pressure: 1,200 PSI
- » MSHA accepted
- » Not to be used on impulse applications

| PART NO. | HOSE ID | HOSE OD | WORKING PRESSURE | MINIMUM BEND PRESSURE | LENGTH |
|--------------|---------|---------|------------------|-----------------------|----------|
| HOSE-PLOK-04 | 1/4 | 1/2 | 375 | 3" | 50'/500' |
| HOSE-PLOK-05 | 5/16 | 9/16 | 300 | 3" | 50'/500' |
| HOSE-PLOK-06 | 3/8 | 5/8 | 300 | 3" | 50'/500' |
| HOSE-PLOK-08 | 1/2 | 3/4 | 300 | 5" | 25'/650' |
| HOSE-PLOK-10 | 5/8 | 29/32 | 300 | 6" | 50'/500' |
| HOSE-PLOK-12 | 3/4 | 1-1/32 | 300 | 7" | 50'/500' |